



Optical Core Alignment Fusion Splicer

DACAS-Digital Analysis Core Alignment Systems

German CNC technique and integrated fiber-adjust frame, which make performance much stable

Fiber type identification function

V-groove precise alignment, high quality and low loss

Auto-splicing mode, using friendly design

5" high resolution color LCD touch screen, 500X magnification, visible clearly with bare eyes

Packed with detachable 5200mAh battery, more than 250 times of splicing and heating


Dust-proof, water-proof, high-temperature resistance, adapting to various altitude and harsh environment

3 high-power white LEDs and illuminated keypads simplifies your work at night


Detachable multifunction fixture, suitable for various fiber type

Built -in Japanese components and Korean chipset

Optical imaging system ranks No. 1 in the world



Integrated fiber-adjust frame



High-power white LEDs



5" touch screen



Fiber endface melter & fusion splicer 2 in 1



STABLE
INTELLIGENT
RELIABLE
FAST

Priority model for backbone project and maintenance

Splicer Master

Optical Core Alignment Fusion Splicer

Combining domestic with foreign technologies, Tumtec has been dedicated to providing professional optical fiber solution and become the renowned fusion splicer & fiber cleaver manufacturer for 15 years.



Standard Accessories

Fusion splicer V9+*1
Fiber cleaver*1
Battery*1
Power adapter*1
AC power line*1
Back-up electrode*1
Cooling tray*1
Carrying case*1
Carrying strap*1
User manual*1
Splicing test report*1
Fiber stripper*1
Drop cable stripper*1
Alcohol bottle*1

Equipment Parameters

Model	V9+
Dimension	130W*170L*170H (excluding rubber bumper) / 140W*170L*176H (including rubber bumper)
Weight	2233G (with battery) / 1853G (without battery)
Number of Fiber	Single
Applicable Fibers	SM(ITU-T G.652& G.657)/MM(ITU-T G.651)/DS(ITU-T G.653)/NZDS(ITU-T G.655)
Compatible Fiber/Cable	0.25 - 3.0mm/Indoor Cable
Cleaved Length	Diameter: 0.125 - 1 mm/Cleave Length: 8-16mm
Cladding Diameter	80 - 150 μ m
Splicing Mode	Pre-set 41 splicing modes, max 100 modes
Heating Mode	Pre-set 5 heating modes (20/30/40/50/60mm), max 100 modes
Typical Splice Loss	SM: 0.02dB / MM: 0.01dB / DS: 0.04dB / NZDS: 0.04 dB / G.657: 0.02dB (ITU-T Standard)
Return Loss	$\geq$ 60dB
Lighting	3 White LEDs
Splicing Time	Quick mode: 6s
Estimated Splice Loss	Available
Heating Sleeve Length	20 - 60 mm
Heating Time	Quick heating time: 13s, typical heating time: 30s
Results Storage	20000 latest records & 200 images
Tension Test	1.96 - 2.25N
Operating Condition	Operating Altitude: 0 - 5000m above sea level, 0 - 95% relative humidity, -10 ~ 50°C Max Wind 15m/s
Storage Condition	0 ~ 95% relative humidity, -40 ~ 80°C
Display	90° bi-directional view, 5.0" Color High Resolution Display
Fiber View & Magnification	X, Y, XY, X/Y: 500X Magnification
Power Supply	AC Input 100 - 240V, DC Input 12 - 15V
No. of Splice/Heating with Battery	5200mAh Battery Capacity, Typical 250 times (Splice + Heat)
Operating Methods	Button/Touch Screen
Automatic Calibration	Automatic arc calibration by air pressure and temperature
Electrode Life	5000 arcs
Terminal	Mini USB 2.0

Tumtec reserve the right to change the design, properties and products without notice. ©2019 print in China



Guangdong Tumtec Communication Technology Co., Ltd

Website: www.gdtumtec.com / www.tumtecchina.com Email: enquiry@tumtec.com Telephone: (+86)757-63509010
Address: Rm 302-1, A5 building Hantian Hi-tech Zone, 17th Shenhai Road, Guicheng Avenue, Nanhai district, Foshan, Guangdong, China.